Binary Tree

This reads words from the standard input, and sorts them in increasing ASCII order. It then prints the words.

```
/*
 * A Word Listing Program
 *
 * Problem:
 *    Given input, print all the words, one per line, and put
 *    line number in front of the word.  A "word" is a maximal
 *    sequence of alphanumeric characters.
 *
 * Author:
 * Matt Bishop (bishop@cs.ucdavis.edu)
 */
#include <stdio.h>
#include <ctype.h>
#include <malloc.h>

/*
 * macros
 *
#define SZBUFFER        1024        /* max length of an input line */

/*
 * the tree node structure
 */
struct node {
      char *word;             /* pointer to word being stored */
      int count;              /* number of times word found */
      struct node *left;      /* points to left subtree */
      struct node *right;     /* points to right subtree */
};
#define N_NULL((struct node *) NULL)/* NULL node pointer */

/*
 * forward declarations (prototypes)
 */
struct node *ninsert(struct node *, char *);    /* insert word into tree */
void nprint(struct node *);                     /* print the tree */
struct node *nalloc(char *);                    /* create a new node */

/*
 * this is the main routine
 *
 * arguments:     ignored
 * return:        exits with 0
 * function:      read from stdin, break each line into words,
 *                add words to binary tree, and when input ends
 *                print the words, one per line, prefixed by count
 *
 * exceptions:    none
 */
void main(void)
```

```
{
      char line[SZBUFFER];          /* input line */
      char word[SZBUFFER];          /* word */
      register int lineno = 0;      /* current line number */
      register char *p;             /* current line position */
      register char *w;             /* used to load line */
      struct node *root;            /* root of the tree */

      /*
       * read the file a line at a time
       */
      while(fgets(line, 101, stdin) != NULL){
            /*
             * begin at the beginning of a new line
             */
            lineno++;
            p = line;
            /*
             * loop until end of line
             */
            while(*p){
                  /*
                   * skip leading non-word stuff
                   */
                  while (*p && !isalnum(*p))
                        p++;
                  /*
                   * stopped at word; put it into word[]
                   */
                  w = word;
                  while(isalnum(*p))
                        *w++ = *p++;
                  *w = '\0';
                  /*
                   * insert it into tree
                   */
                  if (word[0])
                        root = ninsert(root, word);
            }
      }

      /*
       * print the tree
       */
      nprint(root);

      /*
       * say goodbye nicely
       */
      exit(0);
}

/*************** the tree stuff **************/
/*
```

```
 * nalloc: create a node
 *
 * arguments:     char *word  word to be inserted into tree
 * return:        pointer to newly-created node
 * output:        none
 * exceptions:    no memory for node at word %s (returns N_NULL)
 *                no memory for word at word %s (returns N_NULL)
 */
struct node *nalloc(char *word)
{
      register struct node *n;      /* tmp ptr for new node */

      /*
       * allocate the node and space for the word
       */
      if ((n = malloc(sizeof(struct node))) == NULL){
            fprintf(stderr, "no memory for node at word %s\n", word);
            return(N_NULL);
      }
      if ((n->word = malloc((strlen(word) + 1) * sizeof(char))) == NULL){
            fprintf(stderr, "no memory for word at word %s\n", word);
            return(N_NULL);
      }
      /*
       * now set the components of the node and return success
       */
      (void) strcpy(n->word, word);
      n->count = 1;
      n->left = n->right = N_NULL;
      return(n);
}

/*
 * ninsert: insert a word into the binary tree
 *
 * arguments:     struct node *base       root of tree
 *                char *word              word to be inserted into tree
 * return:        pointer to root of tree with word in it
 * output:        none
 * exceptions:    none
 */
struct node *ninsert(struct node *base, char *word)
{
      register int cmp;       /* result of comparison */

      /*
       * see if we have no tree,
       * in which case the new node IS the tree
       */
      if (base == N_NULL)
            return(nalloc(word));
      /*
       * we have one -- where do we go
       */
```

```
	if ((cmp = strcmp(word, base->word)) == 0){
		/* stay here */
		base->count++;
	}
	else if (cmp < 0){
		/* insert in left subtree */
		base->left = ninsert(base->left, word);
	}
	else{
		/* insert in right subtree */
		base->right = ninsert(base->right, word);
	}
	/*
	 * return pointer to root of tree
	 */
	return(base);
}

/*
 * nprint: print the tree inorder
 *
 * arguments:   struct node *base   root of tree
 * return:      nothing
 * output:      count and word, one per line, in order
 * exceptions:  none
 */
void nprint(struct node *base)
{
	/*
	 * no tree means nothing to print
	 */
	if (base == N_NULL)
		return;
	/*
	 * print away!
	 */
	/* print left subtree */
	nprint(base->left);
	/* print node contents */
	printf("%5d\t%s\n", base->count, base->word);
	/* print right subtree */
	nprint(base->right);
}
```