

## Outline for October 11, 2021

**Reading:** §6.9–6.10, 4.9

**Assignments:** Homework 2, due October 20, 2021

1. Example of sets [*sets.py*]
2. String methods: methods that change, add, or delete characters do *not* alter the string to which they are applied; they return a new string that is a copy of the old string, suitably modified
3. String methods: type of characters in string (return `True` or `False`) [*strtype.py*]
  - (a) `S.isalpha()` — `True` if only alphabetic (letters) in `S`
  - (b) `S.isalnum()` — `True` if only alphanumerics (letters or digits) in `S`
  - (c) `S.isdigit()` — `True` if only digits in `S`
  - (d) `S.isspace()` — `True` if only white space (blanks, tabs, newlines) in `S`
  - (e) `S.isupper()` — `True` if all letters in `S` are upper case
  - (f) `S.islower()` — `True` if all letters in `S` are lower case
4. String methods: changing case of letters in string (return result of applying method) [*strchcase.py*]
  - (a) `S.capitalize()` — If the first character of `S` is a letter, capitalize it
  - (b) `S.title()` — Capitalize each word in `S`
  - (c) `S.lower()` — Change all upper case letters in `S` to lower case
  - (d) `S.upper()` — Change all lower case letters in `S` to upper case
  - (e) `S.swapcase()` — Change all upper case letters in `S` to lower case and *vice versa*
5. String methods: stripping blanks from strings (return result of applying method) [*strstrip.py*]
  - (a) `S.lstrip()` — Delete all leading white spaces from `S`
  - (b) `S.rstrip()` — Delete all trailing white spaces from `S`
  - (c) `S.strip()` — Delete all leading and trailing white spaces from `S`
6. String methods: find characters and substrings (return position or cause exception) [*strfind.py*]
  - (a) `S.find(s)` — Return the index of the first occurrence of `s` in `S`; `-1` if `s` not in `S`
  - (b) `S.index(s)` — Return the index of the first occurrence of `s` in `S`; `ValueError` exception if `s` not in `S`
  - (c) `S.rfind(s)` — Return the index of the last occurrence of `s` in `S`; `-1` if `s` not in `S`
  - (d) `S.rindex(s)` — Return the index of the last occurrence of `s` in `S`; `ValueError` exception if `s` not in `S`
7. String methods: miscellaneous [*strmisc.py*]
  - (a) `S.count(s)` — Return the number of times `s` occurs in `S`
  - (b) `S.startswith(s)` — `True` if `S` starts with `s`
  - (c) `S.endswith(s)` — `True` if `S` ends with `s`
  - (d) `S.replace(s, t)` — Replace all occurrences of `s` with `t` in `S`
8. Lists and strings [*datecvl.py*]
9. Program to print words in a line [*lines.py*]